## What Is Claimed Is:

- 1. A device for adjusting guide blades of a gas turbine, where guide blades (12) are each connected to an adjusting ring (17) via an adjusting lever (16), so as to be able to swivel, a first end of the, or each, adjusting lever (16) engaging with the adjusting ring (17), and a second end of the, or each, adjusting lever, opposite to the first end, engaging with an end of a shaft (15) of the respective guide blade (12), wherein the adjusting ring (17) is assigned a rotor of a torque motor, a stator (18) of the torque motor.
- The device as recited in Claim 1, wherein the adjusting ring (17) takes the form of a rotor of the torque motor, a stator (18) of the torque motor concentrically surrounding the adjusting ring (17) and, therefore, the rotor of the torque motor.
- 3. The device as recited in Claim 1 or 2,
  wherein
  the electrical energy required for operating the torque
  motor is provided by a generator (19) of the gas turbine,
  the generator (19) having a stator (21) and a rotor (20),
  and the rotor (20) of the generator (19) taking the form
  of a freewheeling generator turbine, which, driven by a
  gas stream, rotates relative to the stator (21) of the
  generator (19) and thus generates electrical energy from
  the kinetic energy of the gas stream.
- 4. The device as recited in Claim 3, wherein the generator (19) is positioned downstream from a fan

module in such a manner, that the rotor (20) of the generator (19), taking the form of a freewheeling generator turbine, is driven by a gas stream of the fan module.

5. The device as recited in Claim 4, wherein

the generator (19) is integrated into a generator module, the generator module being connected to the fan module at the downstream end of the same, and the generator (19) generating electrical energy from a bypass gas steam of the fan module.

6. The device as recited in one or more of Claims 2 through 5,

wherein

the rotor (20) of the generator (19), taking the form of a freewheeling generator turbine, has a plurality of rotating blades (22), along with pole pieces (24) assigned to the blades (22), the pole pieces being assigned to inner radial ends of the rotating blades (22) of the rotor (20) taking the form of a freewheeling generator turbine, the rotor (20) radially surrounding the stator (18) of the generator (19) from the outside.

7. The device as recited in one or more of Claims 1 through 6,

wherein

the stator (18) of the torque motor and the stator (21) of the generator (19) are supported on a common mount fixture (28), the stator (21) of the generator (19) concentrically surrounding the stator (18) of the torque motor.

8. The device as recited in one or more of Claims 1 through 7,

wherein

the rotor of the torque motor has a plurality of magnetic elements (25) distributed over the circumference of the same.

The device as recited in Claim 8, wherein

the gap between the magnetic elements (25) is dimensioned so that an adjusting lever (16) leading to an adjustable guide blade (12) may be mounted between two adjacent magnetic elements (25).